

WANAFLeX 200

TECHNICAL DATA SHEET OF DIRECTIONAL HOMOGENEOUS VINYL SHEETING

TECHNICAL DATA	STANDARD	UNIT	WANAFLEX
Total Thickness	EN ISO 24346	mm	2
Total Weight	EN ISO 23997	g/m ²	3375
Roll Width	EN ISO 24341	M	2
Roll Length	EN ISO 24341	M	20
SAFETYCRITERIA	STANDARD	WANAFLEX	
Fire Rating	GB8624-2012	B-S1CLASS	
ToxicTesting	GB18586-2001	Good	
Slip Resistance Dry	EN13893	≥ 0.3	
Slip Resistance Dry	DIN 51130	R9	
Electrical Resistance	EN1081	>3.0*1010Ω	
PERFORMANCE	STANDARD	WANAFLEX	
Dimensional Stability	EN434-1994	≤0.4%	
Thermal Conductivity	EN12667	0.050W/(m.k)	
Castor WheelT est	EN425	Suitable	
Wear Resistance	EN660.2	≤3.5MM3	
Abrasion Group	EN649	PGroup	
Residual Indentation	ENISO24343.1	≤0.04MM	
Color Fastness	ENISO105-B02	≥6 degree	
Chemical Product Resistance	ENISO26987	Good	
Antibacterial Property	ENISO846-C	No bacterial	
Hygiene Treatmen	MRSA	Very Good	
Impact Sound Reduction	ENISO10140/1 ENISO 717/2	APPROX.+4DB	
Surface Treatment	EN428	PUR	
Flexibility	EN435	Excellent	

20 Years Commercial Warranty