

WANABIWOOD
INNOVATION THROUGH FLOORING

Product Type	Test Standard	Wanabiwood Exceed 200
Resilient Vinyl Floor	ISO 10581-EN 649	Homogeneous Vinyl Sheet
Product Specification	Test Standard	Wanabiwood Exceed 200
Surface Treatment	ISO 24346(EN 428)	PUR Treatment
Overall thickness	ISO 24326-EN 428	2mm
Roll Width	ISO 24341-EN 426	2M
Roll Length	ISO 24341-EN 426	20M
Total Weight	ISO 23997-EN 430	3250g/m ²
Characteristics	Test Standard	Wanabiwood Exceed 200
Abrasion Group	EN 600-2	P Group
Abrasion Resistance	EN 660-2	<= 2.0 mm ³
Residual Indentation	ISO 24343-EN 433	<= 0.03 mm
Dimensional Stability	ISO 23999-EN 434	<= 0.4%
Castor Chair Test	ISO 4918-EN 425	Suitable
Color Fastness	EN ISO 105-B02	>= 6
Chemical Resistance	ISO 26987-EN 423	Qualified
Antibacterial Property	ISO 846-C	no microbe growth
TVOC after 28 days	ISO 16000-9	<= 10 ug/m ³
Flexibility	ISO 24344-EN 435	Qualified(20mm)
Curling After Exposure to Heat	ISO 23999-EN 434	<= 8mm
Fire Rating	GB 8624-2012	B1 class
Fireproof Degree	EN ISO 13501-1	Bfl-S1
Dop test	EN 14372:2004	No support growth of bacteria
Slip Resistance	DIN 51130	R9 Class
	EN 13893	u>= 0.3
Thermal Resistance	EN ISO 10456	0.01m.K/W
Radiant Floor Heating	EN ISO 10456	Suitable
Static Electrical Propensity	EN 1815	<2.0 KV