

Technical Data Sheet Of Directional Homogeneous Vinyl Sheeting

Technical Data	Standard	Unit	Result
Total Thickness	EN ISO 24346	mm	2
Total Weight	EN ISO 23997	g/m ²	3400
Roll Width	EN ISO 24341	m	2
Roll Length	EN ISO 24341	m	20
Safety Criteria	Standard	Value	
Fire Rating	GB8624-2012	B-S1 CLASS	
Toxic Testing	GB18586-2001	Good	
Slip Resistance Dry	EN 13893	≥ 0.3	
Slip Resistance Wet	DIN 51130	R9	
Electrical Resistance	EN 1081	>3.0*10 ¹⁰ Ω	
Performance	Standard	Value	
Dimensional Stability	EN434-1994	<=0.4%	
Thermal Conductivity	EN12667	0.050 W/(m.k)	
Castor Wheel Test	EN425	Suitable	
Wear Resistance	EN660.2	<=3.5MM ³	
Abrasion Group	EN649	P Group	
Residual Indentation	EN ISO 24343.1	<=0.04MM	
Color Fastness	EN ISO 105-B02	≥6 degree	
Chemical Product Resistance	EN ISO 26987	Good	
Antibacterial Property	EN ISO 846-C	No bacterial	
Hygiene Treatment	MRSA	Very Good	
Impact Sound Reduction	EN ISO 10140/1 EN ISO 717/2	APPROX.+4DB	
Surface Treatment	EN 428	PUR	
Flexibility	EN 435	Excellent	