

TECHNICAL DATA SHEET OF PLATINUM-T

TYPE OF FLOORING MATERIAL DESCRIPTION			Homogeneous Sheet Polyvinyl Chlorid
Total thickness Weight Width of sheet Length of sheet	EN ISO 24346 EN ISO 23997 EN ISO 24341 EN ISO 24341	mm g/sqm meter meter	2 2850 2 20
CLASSIFICATION			
Standard / Product specification European classification Fire rating Electrical resistance Static electrical propensity	EN ISO 10874 EN 13501-1 EN 1081 EN 1815	Class Class Q kV	EN ISO 10581 34 - 43 Bfl-sl 10 ⁹ - 10 ¹⁰ < 2
PERFORMANCE			
Abrasion Group Dimensional stability Impact sound insulation Residual indentation Slip resistance Castor chair test Thermal conductivity Colour fastness Surface treatment Water tightness Chemical products resistance	EN 649 Group EN ISO 23999 % EN ISO 717-2 dB EN ISO 24343 mm DIN 51130 ISO 4918 EN ISO 10456 EN 20 105 - 802	Group % dB mm Class W/ (m. K) degree	T ≤ 0.40 5 < 0.10 R9 ok 0.25 ≥ 7 PUR pass ok > 99 %
Anti-bacterial activity	ISO 22196		inhibits growth 99.7% after 2h
Anti viral activity	ISO 21702		99.9% after 5h